



APC APDU9953 unidad de distribución de energía (PDU) 24 salidas AC 0U Negro

Marca : APC

Código del producto: APDU9953

Nombre del producto : APDU9953


APC APDU9953. PDU tipos: Conmutado, Capacidad del rack: 0U, Tipo: Monofásico. Cantidad de salidas AC: 24 salidas AC, Tipo de salida AC: C13 acoplador, C19 acoplador, Conector: IEC 60309. Voltaje nominal de entrada: 200, 208, 230, 220-240 V, Máxima corriente: 32 A, Frecuencia de entrada AC: 50 - 60 Hz. Certificación: EAC, EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, RCM, VDE. Ancho: 56 mm, Profundidad: 46 mm, Altura: 1829 mm



| Diseño                                     |                                                                       | Condiciones ambientales                           |             |
|--------------------------------------------|-----------------------------------------------------------------------|---------------------------------------------------|-------------|
| PDU tipos *                                | Conmutado                                                             | Intervalo de temperatura operativa                | -5 - 45 °C  |
| Tipo                                       | Monofásico                                                            | Intervalo de temperatura de almacenaje            | -25 - 65 °C |
| Capacidad del rack *                       | 0U                                                                    | Intervalo de humedad relativa para funcionamiento | 0 - 95%     |
| Montaje                                    | Vertical                                                              | Intervalo de humedad relativa durante almacenaje  | 5 - 95%     |
| Color del producto                         | Negro                                                                 | Altitud de funcionamiento                         | 0 - 3048 m  |
| Interruptor de encendido/apagado integrado | ✗                                                                     | Altitud no operativa                              | 0 - 15240 m |
| Puertos e Interfaces                       |                                                                       | Peso y dimensiones                                |             |
| Cantidad de salidas AC *                   | 24 salidas AC                                                         | Ancho                                             | 56 mm       |
| Conector                                   | IEC 60309                                                             | Profundidad                                       | 46 mm       |
| Tipo de salida AC *                        | C13 acoplador, C19 acoplador                                          | Altura                                            | 1829 mm     |
| Control de energía                         |                                                                       | Peso                                              | 7,34 kg     |
| Voltaje nominal de entrada *               | 200, 208, 230, 220-240 V                                              | Empaquetado                                       |             |
| Frecuencia de entrada AC                   | 50 - 60 Hz                                                            | Peso del paquete                                  | 9,95 kg     |
| Máxima corriente *                         | 32 A                                                                  | Ancho del paquete                                 | 165 mm      |
| Capaciad de carga                          | 7400 VA                                                               | Profundidad del paquete                           | 124 mm      |
| Potencia máxima                            | 7360 W                                                                | Altura del paquete                                | 2040 mm     |
| Aprobaciones reguladoras                   |                                                                       |                                                   |             |
| Certificación                              | EAC, EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, RCM, VDE |                                                   |             |



0731304356271



731304356271

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.